

Gel can flow! Now
also from hobbocks.

BEDU
≡ POMPEN ≡

New - Gel-pump for hobbock,
diameter 340 mm

www.gruen-pumpen.de

FIRST KEY DATA

viskosity	grease or gels with follow plate
material pump	stainless steel
tube length	500 mm for Hobbock 30 I, height 403 mm
tube diameter	40 mm
discharge pressure	1 1/4" AG
weight	3,5 kg
temperature limit	80 °C
material seal	carbon, ceramic, viton
rotor	stainless steel 1.4571
stator	PTFE



BEDU
≡ POMPEN ≡

g[®]
grün-pumpen
take out, what's in.

DATA SHEET

positive displacement pump SB40-ds 20.1 PTFE



0,37 kW 230V, switch

0,55 kW 400V, 900/min



pump data		SB40-ds 20.1	
capacity (max)	kg/min	see motor data	
pressure (max)	bar	see motor data	
viscosity		grease or gels with follow plate	
material pump		stainless steel	
tube length	500 mm	for Hobbock 30 l, height 403 mm	
tube diameter	mm	40	
discharge pressure	OT	1 1/4"	
weight	kg	3,5	
temperature limit	°C	80	
material seal		carbon, ceramic, viton	
rotor		stainless steel 1.4571	
stator		PTFE	

SB40-ds 20.1-PTFE-500		ord.-no.	652-0030			
motor data	Weight		pressure	capacity	pressure	capacity
speed 1400/min	kg		bar	kg/min	bar	kg/min
			water		in application	
0,75 kW, 230V, switch, cable	11	500-0075	5	23	depending on viscosity	
0,37 kW, 230V, switch, cable	7	500-0073	1	23		
0,37 kW, 400V, terminal box	7	500-0051	2	23		
0,55 kW 400V, 900/min terminal box	13	500-0078	5	15		

accessories		ord.-no.	
protection switch 400 V		810-0023	
frequency inverter			
follow plate	D=340 mm	840-0250	
hose connection IG 1 1/4"-DN25	DN25	825-0002	safe connection for hose with pump
hose PVC	2m DN25	825-0002	
reduction AG 1 1/4"-IG 1/2"		825-0172 825-0225	adaption to anchor hole
trolley			fastening of the pump, easy moving



045 - 05/2018 www.aaha-design.de Gei: fotolia.de

produced by climate-neutral printing

